

# QUICK START HIGH PRECISION TURNING!!

# ZERO-ZERO HOLDER **PRO** SET

Essential for Ultra-deep hole long drills & Super-precise reamers! The attractive package box to be included with collets, wrenches and spanners comes out now!



PAT.P

**ZERO-ZERO HOLDER**



## **PRO SET (with standard SK collets)**

ZERO-ZERO HOLDER with SK collets, wrenches and spanners

## **PRO SET (with coolant SK-AC collets)**

ZERO-ZERO HOLDER with SK-AC collets, wrenches and spanners

## **FULL SET (with standard SK collets)**

ZERO-ZERO HOLDER with SK collets, wrenches, spanners and Dial Gauges

## **FULL SET (with coolant SK-AC collets)**

ZERO-ZERO HOLDER with SK-AC collets, wrenches, spanners and Dial Gauges

★ Please refer to the back for more details

The above is the set to be included with the dial gauge.

## **Features**

- **Misalignment adjustment range : 0.5mm/diameter**
- **Run-out adjustment range at the tip of 100mm test bar : 0.05**  
**(Cam ring indication :  $\Phi$ 0.1)**

**NIKKEN**

**NIKKEN KOSAKUSHO WORKS, LTD.**  
5-1, 1-chome, Minamishinden, Daito-shi, Osaka-fu, Japan

Web: [www.nikken-kosakusho.co.jp/en](http://www.nikken-kosakusho.co.jp/en)  
Tel: +81-(0)72-869-5820 Fax: +81-(0)72-869-6220  
e-mail: [export@nikken-kosakusho.co.jp](mailto:export@nikken-kosakusho.co.jp)

# ZERO-ZERO HOLDER PRO SET

## ☐ LCH32-SZF16S

### PRO SET (with standard SK collets)

Set Code No.	items	Code No.	
S.LCH32-SZF16S	ZERO-ZERO HOLDER	LCH32-SZF16S-55	
	SPANNER	SKL-16S-P	
	WRENCH	9ZFL	
	CASE	-	
	COLLETS	SK16-6	Chucking Range : 5.5~ 6.0
		SK16-8	Chucking Range : 7.5~ 8.0
		SK16-10	Chucking Range : 9.5~10.0
		SK16-12	Chucking Range : 11.5~12.0
SK16-16		Chucking Range : 15.5~16.0	

## ☐ LCH40-SZF16S

### PRO SET (with standard SK collets)

Set Code No.	items	Code No.	
S.LCH40-SZF16S	ZERO-ZERO HOLDER	LCH40-SZF16S-55	
	SPANNER	SKL-16S-P	
	WRENCH	9ZFL	
	CASE	-	
	COLLETS	SK16-6	Chucking Range : 5.5~ 6.0
		SK16-8	Chucking Range : 7.5~ 8.0
		SK16-10	Chucking Range : 9.5~10.0
		SK16-12	Chucking Range : 11.5~12.0
SK16-16		Chucking Range : 15.5~16.0	

### PRO SET (with coolant SK-AC collets)

Set Code No.	items	Code No.	
S.LCH32-SZF16SC	ZERO-ZERO HOLDER	LCH32-SZF16S-55-A	
	SPANNER	SKL-16S-P	
	WRENCH	9ZFL	
	CASE	-	
	COLLETS	SK16-6AC	Chucking Range : 6.0
		SK16-8AC	Chucking Range : 8.0
		SK16-10AC	Chucking Range : 10.0
		SK16-12AC	Chucking Range : 12.0
SK16-16AC		Chucking Range : 16.0	

### PRO SET (with coolant SK-AC collets)

Set Code No.	items	Code No.	
S.LCH40-SZF16SC	ZERO-ZERO HOLDER	LCH40-SZF16S-55-A	
	SPANNER	SKL-16S-P	
	WRENCH	9ZFL	
	CASE	-	
	COLLETS	SK16-6AC	Chucking Range : 6.0
		SK16-8AC	Chucking Range : 8.0
		SK16-10AC	Chucking Range : 10.0
		SK16-12AC	Chucking Range : 12.0
SK16-16AC		Chucking Range : 16.0	

### FULL SET (with standard SK collets)

Set Code No.	items	Code No.	
S.LCH32-SZF16S-F	ZERO-ZERO HOLDER	LCH32-SZF16S-55	
	DIAL GAUGE	LCD-Z	
	SPANNER	SKL-16S-P	
	WRENCH	9ZFL	
	CASE	-	
	COLLETS	SK16-6	Chucking Range : 5.5~ 6.0
		SK16-8	Chucking Range : 7.5~ 8.0
		SK16-10	Chucking Range : 9.5~10.0
SK16-12		Chucking Range : 11.5~12.0	
SK16-16		Chucking Range : 15.5~16.0	

### FULL SET (with standard SK collets)

Set Code No.	items	Code No.	
S.LCH40-SZF16S-F	ZERO-ZERO HOLDER	LCH40-SZF16S-55	
	DIAL GAUGE	LCD-Z	
	SPANNER	SKL-16S-P	
	WRENCH	9ZFL	
	CASE	-	
	COLLETS	SK16-6	Chucking Range : 5.5~ 6.0
		SK16-8	Chucking Range : 7.5~ 8.0
		SK16-10	Chucking Range : 9.5~10.0
SK16-12		Chucking Range : 11.5~12.0	
SK16-16		Chucking Range : 15.5~16.0	

### FULL SET (with coolant SK-AC collets)

Set Code No.	items	Code No.	
S.LCH32-SZF16SC-F	ZERO-ZERO HOLDER	LCH32-SZF16S-55-A	
	DIAL GAUGE	LCD-Z	
	SPANNER	SKL-16S-P	
	WRENCH	9ZFL	
	CASE	-	
	COLLETS	SK16-6AC	Chucking Range : 6.0
		SK16-8AC	Chucking Range : 8.0
		SK16-10AC	Chucking Range : 10.0
SK16-12AC		Chucking Range : 12.0	
SK16-16AC		Chucking Range : 16.0	

### FULL SET (with coolant SK-AC collets)

Set Code No.	items	Code No.	
S.LCH40-SZF16SC-F	ZERO-ZERO HOLDER	LCH40-SZF16S-55-A	
	DIAL GAUGE	LCD-Z	
	SPANNER	SKL-16S-P	
	WRENCH	9ZFL	
	CASE	-	
	COLLETS	SK16-6AC	Chucking Range : 6.0
		SK16-8AC	Chucking Range : 8.0
		SK16-10AC	Chucking Range : 10.0
SK16-12AC		Chucking Range : 12.0	
SK16-16AC		Chucking Range : 16.0	