


# NPU DRILL CHUCK

**NIKKEN**




3 Times Larger  
Chucking Power

Groove for  
Wrench

BT-NPU

Being given favorable reception for its Compactness, High Precision & High Rigidity.

- The shank body fabricated solidly with the keyless drill chuck eliminates the possibility of slipping-off.
- The attached tightening wrench prevents slipping-off of drill to ensure the safety in unmanned operation.
- Chucking torque three times as large as ever before. There is no possibility of slipping-off of the carbide drill etc.



Chucking Length (  $l$  )  
NPU 8 : 18.8mm  
NPU13 : 26.5mm

TAPER	Code No.	Chucking Dia	D	L		Weight (kg)
				MIN.	MAX.	
No.30	BT30-NPU 8- 70	0.3~8	38	76.5	83.5	0.7
	-NPU13- 95	1~13	48.5	102.1	113.1	1.2
No.40	BT40-NPU 8- 70	0.3~8	38	76.5	83.5	1.2
	(IT40) -110			115.5	122.5	1.5
	-155			160.5	167.5	1.7
	-NPU13- 80	1~13	48.5	86.1	97.1	1.5
	-130			137.1	148.1	2.2
	-175			182.1	193.1	2.7
No.50	BT50-NPU 8- 85	0.3~8	38	87.5	94.5	3.8
	(IT50) -110			115.5	122.5	3.9
	-170			175.5	182.5	4.3
	-NPU13- 90	1~13	48.5	97.1	108.1	4.1
	-130			137.1	148.1	4.6
	-190			197.1	208.1	5.2


★Centre Through Type Drill Chuck has different L-length & Code No. ☞ P.58, Pull Stud with Oil Hole ☞ P.320.  
★Flange Through Type Drill Chuck has different L-length & Code No. ☞ P.58.

★Wrench is available as an option. NPU8: NPUL-8, NPU13: NPUL-13.  
★In case of IT40, IT40-NPU8-80 is the shortest length.  
★In case of IT50, IT50-NPU8-80 is the shortest length.

# Straight Shank NPU DRILL CHUCK

**NIKKEN**

Suitable For MULTI-LOCK Milling Chuck



D-NPU

Style	Code No.	Chucking Dia	L		Weight (kg)
			MIN.	MAX.	
32	D32-NPU 8	0.3~8	65.5	72.5	0.9
	-NPU13	1~13	84.5	96.5	1.4
42	D42-NPU 8	0.3~8	55.5	62.5	1.2
	-NPU13	1~13	79.5	91.5	1.7

★φD : NPU 8 : 36.5mm Chocking Length : NPU 8 : 18.8mm  
NPU13 : 48mm NPU13 : 26.5mm


★Wrench is available as an option.  
NPU8: NPUL-8, NPU13: NPUL-13.

# JACOBS TAPER ADAPTER

**NIKKEN**



JTA



- Taper contact area of more than 80% ensures reliable drilling with no chattering accompanied.

TAPER	Code No. -L	JT. No.	D	H	H1	C	Weight (kg)
No.30	BT30-JTA6-30	6	17.17	24	4	30	1.0
No.40	BT40-JTA6-45, 90						1.1, 1.4
No.50	BT50-JTA6-45, 105						4.0, 4.4

★Each Drill chuck Adapter is supplied without drill chuck.

★For high speed and high accurate application, Slim Chuck ☞ P.41 is highly recommended.