

■テーパシャンクとのインターフェイス

テーパ	Code No.	ドッキング 径Q	L	C	C ₁	H	H ₁	接続ボルト No.	Fig.	重量(kg)
BT	BT30 -Q26- 40	26	40	50	45	18	6	B26N	3	0.5
	BT40 -Q26- 50		50			20				1.1
	- 95		95			65				
	-140		140		110	2.4				
	BT50 -Q26- 65		65		27		3.7			
	-140		140		47	5.3				
	-170N		170		112		2		5.4	
2LOCK NBT	NBT30 -Q26- 40	26	40	50	45	18	6	B26N	3	0.5
	NBT40 -Q26- 50		50			20				1.1
	- 95		95			65				
	-140		140		110	2.4				
	NBT50 -Q26- 65		65		27		3.7			
	-140		140		47	5.3				
	-170N		170		112		2		5.4	
3LOCK MBT	MBT40 -Q26- 50	26	50	50	-	20	-	B26N	1	1.1
	- 95		95			65				1.8
	-140		140			110				
	MBT50 -Q26- 65		65		27	3.7				
	-140		140		47				5.3	
	-170N		170		112	2				5.4
NC5	NC5- 46 -Q26- 40	26	40	50	45	18	6	B26N	6	0.4
	NC5- 63 -Q26- 50		50			20				0.9
	- 95		95			65				
	-140		140			110				2.3
	NC5- 85 -Q26- 65		65		27	2.5				
	-140		140		102		40		4.6	
	-170		170		132	110	4.7			
	NC5-100 -Q26- 65		65		27	-			3.6	
	-140		140		97	45	5.7			
	-170		170		127	110			5	5.8
HSK-A	HSK40A -Q26- 75	26	75	50	33.6	55	40	B26N	6	0.8
	HSK50A -Q26- 75		75		41.6	48	33			1.1
	HSK63A -Q26- 60		60		-	33	-		1.0	
	- 95		95		-	68	-			1.5
	-140		140		-	113	-		2.3	
	HSK100A-Q26- 65		65		33	-	2.4			
	-140		140		106	45			4.5	
	-170N		170		136	110	5			4.6
POLYGONAL TAPER	C6 -Q26- 50	26	50	50	-	27	-	B26N	4	1.1
	C8 -Q26- 60		60			29				2.0
NT	T30W -Q26- 40	26	40	50	-	-	-	B26N	7	0.6
	T40U -Q26- 35		35		-	-	-			1.1
	T40M -Q26- 35		35		-	-	-			
	T50U -Q26- 45		45		-	-	-			3.3
	T50M -Q26- 45		45		-	-	-			
HA	TT35 -Q26- 35	26	35	50	-	-	-	B26	8	0.7
	TT45 -Q26- 45		45		-	-	-			1.8
MT	MT3T -Q26- 45	26	45	50	-	-	-	B26N	9	0.8
	MT4T -Q26- 45		45		-	-	-			1.1
	MT5T -Q26- 35		35		-	-	-			
	MT6T -Q26- 60		60		-	-	-			5.1
K	K32 -Q26- 40	26	40	50	-	-	-	B26N	10	0.8
	K42 -Q26- 40		40		-	-	-			1.3

★接続ボルト及びレンチは付属しています。 ★全シリーズ スルーホール対応です。 ★上記以外のシャンクも対応可能です。別途ご相談下さい。