

# **Tilting Rotary Table with AR21 Controller**



### 5AX-550WAR21




The specification of the large rotary table will be varied according to your application.



Motor capacity of rotary axis and tilting axis are added at the end of Code No. e.g 5AX-550WAR21-1818

### 5AX-800WAR21






Motor capacity of rotary axis and tilting axis are added at the end of Code No. e.g 5AX-800WAR21-1875

### 5AX-1200BWAR21





Motor capacity of rotary axis and tilting axis are added at the end of Code No. e.g 5AX-1200BWAR21-4444

- 1. Moving angle of the tilting axis
- 2. Relation between the tilting axis center and the rotary axis



5AX-1200A: The tilting axis center is located in the same position as the center of the rotary axis body.





5AX-1200B: The tilting axis center is located in the same position as the top surface of the rotary axis.


- 3. Tilting axis base...It can be supplied to us.
- 4. With/ witout T slot, Width of T slot
- 5. Spindle hole dimension
  - ... Center socket for centering is normally attached.

## 5AX-2MT-105WAR21










Clamp Device



Motor capacity of rotary axis and tilting axis are added at the end of Code No. e.g 5AX-2MT-105WAR21-0404 If you need a knock hole for positioning or a key way on the table surface, please contact us.

AR21 controller can drive the all models of NIKKEN rotary tables. Please contact us for the external dimension.



Back side motor mounted CNC rotary table





Top side motor mounted CNC rotary table

Indexing of MIN. incremental of 1° is done by AR21 controller.



Multi-spindle CNC rotary table





AR21 controller can perform indexing of MIN. 1° with hirth coupling and can also perform indexing of MIN. incremental by 0.001° and profile milling.